

WHAT IS CLAIMED IS:

1. A method of forming a compact disposable police restraint comprising the steps of:
 - (a) selecting a cuff device comprising at least one elongated, substantially flat strap, connected to a toothed socket clasp;
 - (b) rolling the flat strap of the cuff device into a coil; and
 - (c) securing the coil with a banding device.
2. A compact disposable police restraint formed by the method of claim 1.
3. The method of claim 1, wherein the cuff device comprises a single substantially flat, toothed strap and a single slot, toothed socket clasp at one end thereof.
4. A compact disposable police restraint formed by the method of claim 3.
5. The method of claim 3, wherein the flat strap is rolled so as to leave the toothed socket clasp on the outside of the coil.
6. A compact disposable police restraint formed by the method of claim 5.
7. The method of claim 3, wherein the flat strap is rolled so as to place the toothed socket clasp on the inside of the coil.
8. A compact disposable police restraint formed by the method of claim 7.

Sub 21 9. ~~The method of claim 1, wherein the cuff device comprises two substantially flat, toothed straps and a two slot, toothed socket clasp at one about the midpoint of said straps.~~

10. A compact disposable police restraint formed by the method of claim 9.

11. Apparatus for manufacturing a compact disposable police restraint, said apparatus comprising two spaced apart, rotatable mandrels, which when rotated will form coils from an elongated, substantially flat strap of a cuff device attached thereto.

12. The apparatus of claim 11, wherein the mandrels are slotted through the center, with the slots having the shape of a radius.

13. The apparatus of claim 12, wherein the mandrels are counter rotated using drive gears, such that they move toward one another in order to coil the cuff sections tight against each other.

14. The apparatus of claim 13, wherein the drive gears which move the counter rotating mandrels are powered by a motor.

15. The apparatus of claim 11, further comprising a movable plate, mounted over the two mandrels, so that the cuff, once it has been tightly coiled and secured with a band, can be ejected from the mandrels.

16. The apparatus of claim 15, further comprising a yoke with a handle, attached to the movable plate, which forces the plate forward to eject the coiled and banded cuff.

Sub B6

17. A disposable handcuff comprising a single coiled toothed strap with a single slot, toothed socket clasp at one end thereof.

18. The disposable handcuff of claim 17, further comprising a banding device holding the coil in place.

data 2

19. A disposable handcuff comprising two coiled toothed straps and a two slot, toothed socket clasp at one about the midpoint of said straps.

20. The disposable handcuff of claim 19, further comprising a banding device holding the coils in place.

add
CH
DII

add
B6